

Ovation P-56VW



SPECIFICATIONS

Optical

- Light Source: 48 LEDs (6 red, 6 green, 10 blue, 4 R. blue, 6 orange, 16 lime) 3 to 4 W, (1 A), 50,000 hours life expectancy
- Color Temperature (range): 2800 to 8000 K
- CRI: 92-93
- Beam Angle (Medium lens): 21°
- Beam Angle (Wide lens): 54°
- Beam Angle (Wide lens w/ egg crate): 40°
- Field Angle (Medium lens): 35°
- Field Angle (Wide lens): 84°
- Field Angle (Wide lens w/ egg crate): 66°
- Lumens (Medium Lens): 3,967
- Lumens (Wide Lens): 4,476
- Illuminance (Medium Lens): 1220 lux @ 5 m
- Illuminance (Wide Lens): 220 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4000 Hz, 6,000 Hz, 25000 Hz

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 29 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

FEATURES

- Variable white PAR-style fixture with homogenized single source of light
- Interchangeable lens plates included for medium and wide beam angles
- Soft, even field of light
- Quiet operation for use in any situation with fan speed control
- +/- Green adjustment via DMX or on-board control
- Independent color control over the 6-color engine when a splash of color is needed
- RDM and variable Pulse Width Modulation for setup ease
- Accepts standard 7.5" beam shaping accessories
- 16-bit dimming resolution for smooth fades
- Professional Clamps: CTC-50HC, CTC-50HCN
- Neutrik® powerCON® cables
- 3-pin or 5-pin DMX Cables
- Color Blending Filters: DF60X1D, DF20D
- Ovation F 7.5" Barn door
- Ovation 60 deg, 7.5" Honeycomb

Optional Accessories

Construction / Physical

- Dimensions: 12.48 x 12.83 x 14 in (317 x 326 x 363 mm)
- Weight: 12 lb (5.5 kg)
- Exterior Color: Black
- Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

Connections

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: DMX, RDM
- DMX Channels: 3, 5, 6, 8, 11, 15 or 17
- Modes/Personalities: 7 personalities (3, 5, 6, 8, 11, 15, 17)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 7 units @ 120 V; 13 units @ 208 V; 14 units @ 230 V
- Power and Current: 175 W, 1.505 A @ 120 V, 60 Hz
- Power and Current: 166 W, 0.879 A @ 208 V, 60 Hz
- Power and Current: 165 W, 0.801 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET, FCC
- IP Rating: IP20, dry location
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

- Ovation P-56VW
- Neutrik powerCON power cord
- Gel frame holder (7.5 in/191 mm accessories)
- Wide and Medium Lenses