

Ovation Rêve P-3 IP

SPECIFICATIONS

Optical

- Light Source: 80 LEDs (10 red, 10 green, 10 blue, 20 amber, 30 mint) 4.4 to 7.8 W, (2.4 A), 50,000 hours life expectancy.
- Color Temperature (range): 2800 to 8000 K
- Color Temperature (at full): 5399 K
- Beam Angle (Narrow Lens): 11.9°
- Beam Angle (Medium Lens): 25.6°
- Beam Angle (Wide Lens): 29.3°
- Beam Angle (Very Wide Lens): 43.5°
- Field Angle (Narrow Lens): 20.8°
- Field Angle (Medium Lens): 37.8°
- Field Angle (Wide Lens): 43.1°
- Field Angle (Very Wide Lens): 87.9°
- Lumens (Narrow Lens) : 10,051
- Lumens (Medium Lens) : 10,079
- Lumens (Wide Lens) : 9,936
- Lumens (Very Wide Lens) : 8,380
- Illuminance (Medium Lens) : 1,950 lux @ 5 m
- Illuminance (Wide Lens) : 1,475 lux @ 5 m
- Illuminance (Very Wide Lens) : 401 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

FEATURES

- Full-spectrum LED PAR lighting fixture for rental/production use as well as special event and theatre.
- Fully IP65 rated for seasonal use indoors or out
- Interchangeable Narrow, Medium, Wide lenses.
- USB port for fixture software updates
- Linear color temperature presets from 2800 K to 8000 K with high CRI and CQS
- +/- Green adjustment and emulated red-shift via DMX or on-board control

Construction / Physical

- Dimensions: Dimensions: 18.82 x 11.81 x 8.27 in (478 x 300 x 210 mm)
- Weight: 21.4 lb. (9.8 kg)
- Exterior Color: Black
- Housing Material: Aluminum diecast
- Accessory Holder/Gel Frame Size: 7.5 in (191 mm)

Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)
- Software Connection: USB

Control

- Control Protocol: DMX, RDM
- DMX Channels: 1, 4, 5, 7, 11, 13ch1, 13ch2, 17 or HSV
- Modes/Personalities: 9 personalities (1, 4, 5, 7, 11, 13ch1, 13ch2, 17, HSV)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 5 units @ 120 V; 8 units @ 208 V; 9 units @ 230 V;
- Power and Current: 274 W, 2.31 A @ 120 V, 60 Hz
- Power and Current: 267 W, 1.38 A @ 208 V, 60 Hz
- Power and Current: 265 W, 1.25 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET, FCC, UKCA
- IP Rating: IP65, outdoor/wet, with pressure equalizing M12 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

What's Included

Dynamic Effects

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 25 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Dim Modes: 4
- Built-in Automated Programs: Yes

Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Safety Cable: SC-07
- TRUE1 Style Power Extension Cables
- 5-pin IP65 DMX Cables
- RDM2go
- USB Jump Drive
- Ovation F 7.5" Barndoor V2

- Ovation Reve P-3 IP
- Seetronic Powerkon power cord
- Narrow, Medium, Wide, Very Wide Lens
- Gel Frame Holder