







EMPOWERING YOUR ECO FREEDOM

WATTMAN




ZERO EMISSION GENERATOR*

Energy anywhere, quietly and without pollution




CONFORTABLE

-  Light weight
-  Mobile
-  Silent, odourless
-  Very powerful

DURABLE

-  Robust
-  Long-life battery
-  Locally repairable

ECO-FRIENDLY

-  0 CO2 emissions during use
-  13 tonnes of CO2 avoided after 5 years of use
-  Solar recharge compatible

*IN USE

Retractable handlebar, multiple carrying handles, off-road wheels, your best partner on set



Wattman Technical data

ELECTRIC

Rated output power	6000 W
Peak power	12000 W
Battery capacity	10000 Wh
Battery service life (>80%)	2000 cycles
Output voltage	230 VAC- 50hz
Charging time (domestic socket 16 A)	<4h
Solar charging compatible	
AC output	2 Type E-16A (2 x 3500 W) 1 P17 - 32A ou Maréchal mono 50A
AC input	1 Power Twist NCA3 - 20A 1 Anderson socket 50 A (PV 5000 W)
Solar charging	120-400 Vdc, 6000W max

TEMPERATURE

Temperature of use	-10 C° à 45 C°
Temperature on charge	-20 °C à 45 °C

ENVIRONNEMENT

Standards	IP22, IK07
Noise level in inverter mode	< 20 dB
Noise level in charger mode	< 30 dB
CE Certification	Directive BT (2014/35/UE) et CEM (2014/30/UE)

PHYSICAL

Dimensions (closed handlebars)*	51,2 x 64,5 x 63 cm
Weight	90 kg
LCD strip (charge status)	
Off-road wheels	
Powder-coated reinforced sheet steel frame	
Raised chassis for crossing standard pavements	
LCD display	

OPTIONS

Extended warranty	
Maintenance contract	
Rain cover	
Hot swap system « InfiniT »	
EKLA mobile solar panel range	



*dimensions including wheels