

# Shocker Panel FX

## HIGHLIGHTS

- Versatile blinder, wash and strobe light with brilliant eye candy effects
- 16 controllable sections (8 RGB + 8 white) allows for creative programming flexibility
- Rugged, all-metal housing makes it ideal for mobile application
- Trigger eye-catching built-in macros via the display or DMX
- powerCON®-compatible power input/output connections for power linking
- Easily transports in the optional CHS-25 VIP gear bag

## SPECIFICATIONS

- DMX Channels : 4, 7, 18, 34 or 47
- DMX Connectors : 3- and 5-pin XLR
- Light Source : 480 LEDs (tri-color) 2 W, (1 A), 50,000 hours life expectancy
- 32 LEDs (cool white) 1.1 W (0.4 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 119°
- Field Angle : 158°
- Illuminance : 1,131 lux @ 2 m
- Lumens : 13,626
- Power Linking : 5 units @ 120 V; 10 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 296 W, 2.5 A @ 120 V, 60 Hz
- 281 W, 1.3 A @ 230 V, 50 Hz
- Weight : 8.6 lb (3.9 kg)
- Size : 12.63 x 4.3 x 6.7 in (310 x 110 x 170 mm)
- Approvals : CE, UKCA , ROHS

## WHAT'S INCLUDED

- Shocker Panel FX
- Power cord
- QRG

